



SPECIFICHE

Schema ottico	16 elementi in 13 gruppi
Apertura minima	F16
Angolo di ripresa	Sony E-Mount 83.2° Canon EF-M Mount 79.9° Micro Four Thirds Mount 68.1° L-Mount 83.2° FUJIFILM X Mount 83.2°
Distanza di messa a fuoco minima	25 cm / 9.8 in.
Dimensioni (diametro x lunghezza)	Sony E-Mount $\phi 72.2\text{mm} \times 92.3\text{mm} / \phi 2.8\text{in.} \times 3.6\text{in.}$ Canon EF-M Mount $\phi 72.2\text{mm} \times 92.3\text{mm} / \phi 2.8\text{in.} \times 3.6\text{in.}$ Micro Four Thirds Mount $\phi 72.2\text{mm} \times 91.1\text{mm} / \phi 2.8\text{in.} \times 3.6\text{in.}$ L-Mount $\phi 72.2\text{mm} \times 90.3\text{mm} / \phi 2.8\text{in.} \times 3.6\text{in.}$ FUJIFILM X Mount $\phi 72.2\text{mm} \times 92.6\text{mm} / \phi 2.8\text{in.} \times 3.6\text{in.}$
Lamelle del diaframma	9
Massimo rapporto d'ingrandimento	1:9.9
Peso	Sony E-Mount 405g / 14.3oz. Canon EF-M Mount 405g / 14.3oz. Micro Four Thirds Mount 395g / 13.9oz. L-Mount 415g / 14.6oz. FUJIFILM X Mount 405g / 14.3oz.
Diametro del filtro	$\phi 67\text{mm}$